

**CITY OF TALENT  
PUBLIC WORKS DEPARTMENT  
STORM DRAIN PROTECTION PERMIT**

In order to achieve compliance with the Oregon Department of Environmental Quality's (DEQ) National Pollutant Discharge Elimination System (NPDES) Phase II Municipal Stormwater requirements, the Rogue Valley Sewer Services (RVS) is now enforcing Chapter 4.05 of the Stormwater Management ordinance in the cities of Central Point, Phoenix, and Talent and designated areas of Jackson County. This Storm Drain Protection permit is required for any ground disturbing activities.

Projects must comply with the minimum requirements specified below and on the attached diagram to remain consistent with the Phase II requirements and Chapter 4.05 of the Stormwater Management ordinance. RVS will be conducting inspections of developments, including projects less than 1 acre, for compliance with the above ordinance. It is important to note that additional erosion and sediment controls may be necessary, depending on site conditions, weather, construction methods, etc., to prevent pollutants from entering the stormwater system. Projects larger than 1 acre may need to meet DEQ's 1200-C permit requirements.

The minimum stormwater protection requirements are as follows:

1. The property owner shall implement the appropriate measures to prevent debris, dirt, petroleum products, pesticides, fertilizers, cement washout, paint, or any hazardous materials from being washed into the storm sewer system. In the event such materials are placed or accidentally deposited outside the property boundary they shall be immediately cleaned up and removed.
2. The property owner shall obtain written authorization from the City prior to placing fill on private or public property. No piles of dirt, rock, bark or any other materials shall be placed in the street or curb/gutter.
3. Parking must be on the street unless a city approved staging area is designated for parking. All parking areas must be protected to prevent track out.
4. All concrete equipment must be washed in a contained concrete washout. Tile cutters, pipe cutters, and concrete/grout pumps must have a tarp or other protective material placed under the equipment to collect cuttings, dust, or spills. Waste materials shall be properly disposed of and not washed into the storm sewer system.
5. Any access off paved areas shall have a gravel entrance/exit. The gravel must have a minimum 8-inch depth of 3-6 inch or smaller crushed rock placed over filter fabric that extends from the street to 30 feet beyond the edge or to the garage at the full width of the entrance.
6. Exposed soils shall be protected from excessive erosion by the use of erosion prevention measures (i.e. fabric, matting, hydro-seeding, etc.) between October 1<sup>st</sup> and May 31<sup>st</sup>. Areas with steep slopes may require special erosion protection.
7. All material piles shall be bordered with sediment control measures and, when not in use, protected with erosion prevention measures between October 1<sup>st</sup> and May 31<sup>st</sup>.
8. Porta-potties must be located off the public right-of-way and at least 30 feet from any catch basin.
9. Best Management Practices (BMP) shall be cleaned and/or repaired as necessary to facilitate proper operation during construction and removed when the site has been stabilized to prevent pollutant runoff.

By signing you are claiming to be the responsible party for work on the subject site specified below and accept full responsibility for any violations of RVS' Chapter 4.05 Stormwater Management ordinance. You understand and accept the conditions set forth in this permit and understand there are penalties for failure to comply.

Signature: \_\_\_\_\_ Date: \_\_\_\_\_

Printed Name: \_\_\_\_\_ Contact #: \_\_\_\_\_

Site Address or Map and Tax Lot Number: \_\_\_\_\_